Conforms to SS 586-3 - GHS -Singapore

BUCHER

SAFETY DATA SHEET

emhart glass 1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 1. Identification

GHS product identifier : 1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set,

1320-455 R-220 Orifice Ring Luting Cement

Other means of identification

: Not available.

Product type : Solid.

Relevant identified uses of the substance or mixture and uses advised against

Refractory Ceramic Mortar.

Supplier's details : EMHART Glass Manufacturing Inc.

405 East Peach Street

PO Box 580

Owensville MO 65066 USA Tel: +1 573 437 2132 Fax: +1 573 437 3146

Emergency telephone number (with hours of operation)

: CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

(24/7)

Section 2. Hazards identification

Classification of the substance or mixture

: CARCINOGENICITY - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements: May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Use personal protective equipment as required. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash

hands thoroughly after handling.

Response : Get medical attention if you feel unwell. IF exposed or concerned: Get medical

attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 2. Hazards identification

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of : Not available.

identification

CAS number/other identifiers

CAS number : Not applicable. **EC** number : Mixture.

Product code : 1320-25, 1320-40, 1320-455

Ingredient name	%	CAS number
Crystalline silica respirable	10 - 30	14808-60-7
Cristobalite	1 - 5	14464-46-1
Titanium dioxide	1 - 5	13463-67-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Chemical formula : Not applicable.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of

water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get

medical attention immediately.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Get medical attention immediately.

: In case of contact, immediately flush skin with plenty of water for at least 20 minutes Skin contact

while removing contaminated clothing and shoes. Get medical attention

immediately.

: Wash out mouth with water. Do not induce vomiting unless directed to do so by Ingestion

medical personnel. Never give anything by mouth to an unconscious person. Get

medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eve contact No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.



1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 4. First-aid measures

Skin contact

: No known significant effects or critical hazards.

Ingestion

: No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: No specific fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: No special measures are required.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up



Section 6. Accidental release measures

Spill

: Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Crystalline silica respirable	Factories Order (PEL) (Singapore, 2/2006). PEL (long term): 0.1 mg/m³ 8 hours. Form: Respirable Dust
Cristobalite	Factories Order (PEL) (Singapore, 2/2006). PEL (long term): 0.05 mg/m³ 8 hours. Form: Respirable
Titanium dioxide	Dust Factories Order (PEL) (Singapore, 2/2006). PEL (long term): 10 mg/m³ 8 hours.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists

or dusts.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a risk assessment indicates

this is necessary.

Body protection: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Use a properly fitted, particulate filter respirator complying with an approved

standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and

the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Solid. [Granular]

Colour : Off-white.

Odour : Odourless.

Odour threshold : Not available.

pH : 10 to 11 [Conc. (% w/w): 1%]

Melting point : Not available. : Not available. **Boiling point** Flash point : Not applicable. **Burning time** : Not applicable. **Burning rate** : Not applicable. : Not available. **Evaporation rate** : Not available. Flammability (solid, gas) Lower and upper explosive : Not applicable.

(flammable) limits

Vapour pressure : Not applicable.
Vapour density : Not available.
Relative density : Not available.
Solubility : <5% in water.
Solubility in water : Not available.
Partition coefficient: n- : Not available.

octanol/water

1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 9. Physical and chemical properties

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: Inert material.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SADT : Not available.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

There is no data available.

Irritation/Corrosion

Skin : There is no data available.Eyes : There is no data available.Respiratory : There is no data available.

Sensitisation

Skin : There is no data available.

Respiratory : There is no data available.

Carcinogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.



1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 11. Toxicological information

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

Potential delayed effects

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

Long term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

Potential chronic health effects

Potential delayed effects

General : Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.



1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 14. Transport information

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

History

Date of issue 2013/12/15

Version : 1

Revised Section(s) : Not applicable.

Prepared by KMK Regulatory Services Inc.

ATE = Acute Toxicity Estimate **Key to abbreviations**

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified

by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations





1320-25 No. 353A Cement, Air Set, 1320-40 No. 353H Cement, Heat Set, 1320-455 R-220 Orifice Ring Luting Cement

Section 16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

